# TANGO FLINT





## **CLEANING**

S: Solvent Cleaner - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

#### **CATEGORY**

Upholstery

## **PROPERTIES**



## CONTENT

100% Polyester

## **BACKING**

Acrylic

#### **FINISH**

Stain Repellent - PFOA & PFOS Free

#### **WIDTH**

57"

#### **WEIGHT**

17.27 oz./linear yard

## **SHOWN RAILROADED**

No

## DIRECTIONAL

No

## **ROLL LENGTH**

38-55 yards

## **VISUAL REPEAT**

4.8" H, 4.8" V

#### **BREAKING STRENGTH**

Warp 246/Fill 282

## SEAM STRENGTH

Warp: 96/Fill: 84

## **ABRASION RESISTANCE**

Passes 80,000 Double Rubs (Wyzenbeek)

#### **PILLING RESISTANCE**

Class 5

## **COLORFASTNESS TO CROCKING**

Dry: Class 4 min/Wet: Class 4 min

## **COLORFASTNESS TO LIGHT**

40 hours

## **APPLICATION**

Indoor

## **TANGO FLINT** 460-006



#### **FLAMMABILITY**

Passes Cal 117-2013; NFPA 260/UFAC Class 1; May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

## WARRANTY

Standard Upholstery | '5' Five Year Warranty



Certified

