FEDORA TANGELO

621-019





CLEANING

W: Water-Based Cleaner - Spot clean, using the foam only from a water-based cleaning agent, such as a mild detergent or non-solvent upholstery shampoo product. Apply foam with a soft brush in a circular motion. Always rinse promptly with clean water. Vacuum when dry. Pretest small area before proceeding.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Upholstery & Panel

PROPERTIES



CONTENT

100% Polyester

BACKING

Polyester

FINISH

Stain Repellent - PFOA Free

WIDTH

54"

WEIGHT

17.2 oz./linear yard

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

50 yards

BREAKING STRENGTH

Warp 290/Fill 239

SEAM STRENGTH

Warp: 106.1/Fill: 109.2

ABRASION RESISTANCE

Passes 100,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE

Class 5

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT

40 hours

FLAMMABILITY

Passes Cal 117-2013; NFPA 260/UFAC Class 1; ASTM E84 Class 1 or A; May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

FEDORA TANGELO 621-019



WARRANTY

Standard Upholstery | '5' Five Year Warranty

GREENGUARD GREENGUARD GOLD Certified Certified



